

وصف المنتج

shower •

pre-mounted rough-in set 9.5 l/min for head shower (26 484) •

pre-mounted wall outlet for hand shower •

pre-mounted and insulated mixed water pipes •

for on-the-wall installations or dry-cladding •

• إطار من الصلب مغطى بالمسحوق، ذاتي الدعم

completely pre-assembled •

• عمق قابل للضبط

• مدخلان سفليان، $1/2$ بوصة

min. installation depth (from rough wall to end finish) 77-107 mm •

min. installation depth (from rough wall to frame front) 67 mm •

head shower outlet height adjustable by 180 mm •

sealing fleeces •

leak test done ex factory •

suitable for concealed 3-function trim sets in combination with GROHE

Rápido SmartBox •

suitable for GROHE shower outlet elbows with male connection threads.

 $1/2'' \cdot$

suitable for Rainshower SmartActive 310 2-spray head shower with 430

mm shower arm •

for on-the-wall installation please order wall brackets 103 999 9990

(sold separately) •



10 399 499 90 RAPIDO SHOWER FRAME ELEMENT FOR DUO CONCEALED SHOWER INSTALLATION

قطعة الغيار

1: طقم عزل (رقم الطلب: 48263000)

هذه رايل غل، اعطى اقل عسوم وضع رفوتي ال

2: حوامل حائطية * (رقم الطلب: 1039999990)

* إكسسوارات اختيارية